



fluortubing

FLUORFLOW

Fluortubing's Fluorflow® PTFE Tubing combines a smooth inner surface with a corrugated exterior, offering excellent fluid flow, flexibility and mechanical strength.



- Superior Flexibility & Flow
- Wide Temperature & Chemical Resistance
 - Reinforced for High Pressure
 - Multiple Industry Certifications

Durable Protection: 316SS Braid & Silicone Coating

- 316SS Braid – Enhances mechanical strength, pressure resistance, and prevents kinking.
- Silicone Coating – Protects the braid, prevents dirt buildup, and is easy to clean.
- PTFE Inner Layer – Ensures zero interaction with the medium, preventing contamination.

Durable Protection: 316SS Braid & Silicone Coating

Nominal Hose Bore (Inch)	Minimum Bend Radius (MM)	Maximum Working Pressure (BAR)	Minimum Burst Pressure (BAR)
1/4	19	80	320
5/16	19	80	320
3/8	25	80	500
1/2	38	70	400
5/8	51	65	380
3/4	63	60	300
1	100	50	200
1 1/4	140	45	180
1.5	171	40	160
2	210	30	120
2.5	304	20	80

FDA 21 CFR 177.1550	USP Class 6	ISO 10993
EN 16663	CE 1935/2004	CE 10/2011
REACH & ROHS	L929 MEM	TUV NORD TUV NORD Nederland B.V. ISO 9001



M: +91 72080 30921



sales@fluortubingindia.com



www.fluortubingindia.com